



ELASTIFICANTE WANDA 5100

Quick Reference



Use Elastificante ruler



To add hardener, use the specific primer, clear or 2K topcoat ruler.



Description: Product designed to promote primers, 2K topcoat and clears flexibility, on plastic substrates.

Products and additives: Elastificante Wanda 5100 – 408.02000

Basic raw materials: Polyester resin and solvents.

Mixing ratio:

Products	Elastificante 5100
Primers PU	50%
Clears and 2K topcoat	30%

Process:

Primer: add 50% of Elastificante (volume). Homogenize it and add the hardener, following the primer mixing ratio. It is not necessary a thinner addition.

Clear and 2K topcoat: add 30% of Elastificante (volume) Homogenize it and add the hardener, following the clear or 2K topcoat mixing ratio. It is not necessary a thinner addition.

Spraying process: Follow the specific process of the product that the Elastificante is being used with.

Cleaning of equipment: Use Thinner Wanda 1100 – 407.04000

Shelf life: 3 years at temperatures between 15°C and 35°C, no humidity.

Health and Safety data: Please refer to MSDS

Observations:

These products are intended for professional use only. Please, refer to can, Technical Data Sheet and Safety Data Sheet form more specific information. These products are thoroughly controlled and their quality will be kept as long as they are used according to the manufacturer recommendations. The final result depending upon factors of use which are outside our control.



Notes:

-Elastificante has to be added to the product before the hardener adding.

Observations:

These products are intended for professional use only. Please, refer to can, Technical Data Sheet and Safety Data Sheet form more specific information. These products are thoroughly controlled and their quality will be kept as long as they are used according to the manufacturer recommendations. The final result depending upon factors of use which are outside our control.

