



## REMOVEDOR PASTOSO

### Quick Reference



Ready to use



Apply thin layers



Keep it protected from the sun

<b>Description:</b>	Product based on strong chemicals, indicated to remove old paint coatings.
<b>Products and additives:</b>	Removedor Pastoso: 408.00396
<b>Basic raw material:</b>	Cellulose resin and solvents.
<b>Mixing ratio:</b>	Ready to use
<b>Process:</b>	Apply a thin layer with a brush. Wait for 5 minutes. Following, remove the material with a spatula. Repeat this process until total removal of coatings.
<b>Theoretical cover rate :</b>	4,4 m <sup>2</sup> /liter/coat
<b>Cleaning of equipment:</b>	Use Thinner Wanda 1100 - 407.04000
<b>Shelf life:</b>	1 year at temperatures between 15°C and 30°C, no humidity.
<b>Health and Safety data:</b>	Wear suitable mask with chemical filter to organic vapors during the application. Protect hands with gloves and wear goggles. Please refer to MSDS.
<b>Notes:</b>	-Use cloth or paper on the tip to open the can and open it carefully due to the gases escape. -Do not apply it on hot surface or under the sun.

### Observations:

These products are intended for professional use only. Please, refer to can, Technical Data Sheet and Safety Data Sheet form more specific information. These products are thoroughly controlled and their quality will be kept as long as they are used according to the manufacturer recommendations. The final result depending upon factors of use which are outside our control.



**Observations:**

These products are intended for professional use only. Please, refer to can, Technical Data Sheet and Safety Data Sheet form more specific information. These products are thoroughly controlled and their quality will be kept as long as they are used according to the manufacturer recommendations. The final result depending upon factors of use which are outside our control.

